

SPECIFICATIONS




PARAMETERS	VALUES	UNITS
RATED VOLTAGE	4.5	Vdc
OPERATING VOLTAGE RANGE	3 ~ 6	Vdc
RATED CURRENT (MAX)	20	mA
MINIMUM SPL @ 10 CM	79	dBA
RESONANT FREQUENCY	400 ± 100	Hz
TONE OR PULSE RATE	CONTINUOUS	0 pulse/sec
OPERATING TEMPERATURE	-20 ~ +65	°C
STORAGE TEMPERATURE	-30 ~ +75	°C
HOUSING MATERIAL	ABS	-
TERMINAL MATERIAL	LEAD WIRE	-
WEIGHT	9	grams

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO
PUI AUDIO, INC. ANY USE OR REPRODUCTION, IN
ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION
OF PUI AUDIO, INC. IS PROHIBITED.

©2010, PUI AUDIO Inc.

REVISION HISTORY			
ITR	DESCRIPTION	DATE	APPROVED

LTR	DESCRIPTION	DATE	APPROVED
-	RELEASED FROM ENGINEERING	5/30/2006	
A	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	12/17/2007	B.R.
B	REVISED SPL, NOTCH DIMENSION, ROHS STATUS	9/23/2013	M.L.
C	REVISED TEMPERATURE RATINGS	2/14/2020	M.L.



NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
3. THIS PART IS RoHS 2015/863/EU COMPLIANT.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS, TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.	SIZE A3	Designed by	Date	Checked by	Date	Approved by	Date	Drawn Date	
		J.D.	5/30/2006	E.P.	5/30/2006	B.R.	5/30/2005	12/18/2007	
	 pui audio TM inc a projects unlimited company				AI-2304-TF-LW120-5V-R				
AI-2304-TF-LW120-5V-R.idw		Indicator					Edition -	Sheet 1 / 1	