

1		2		3		4		5		6		7		8	
CUSTOMER No. :		REV .		CATEGORY		IN IINE WITH THE TYPE		PAGE	REV .	ECN&ECR No.	DESCRIPTION		DSN	DATE	
						YES NO			C1	NA	Initial Drawing		XU	2022.05.27	
				NEW ENERGY VEHICLE PRODUCTS		√									
				INDUSTRIAL PRODUCTS		√									
				RoHS		√									
				REACH											
				Halogen-Free		√									
				CALIFORNIA 65		√									

15±0.1

Ø16.0±0.1

Panel Cut-Out

2 RED

WHITE 3

1 BLACK

VIEW A

19REF

Panel T=2.5Max

10REF

P1

①

②

③④⑤

*500±30

P/N: 22003635-01

SPECIFICATIONS:

1.INSULATION RESISTANCE: 10MΩ@500VDC/0.01S.

2.VOLTAGE RATING: 600V.

3.CURRENT RATING: 10A.

4.OPERATION TEMPERATURE: -10℃~+105℃.

5.WATERPROOF IPX7(MATED).

6.RoHS COMPLIANT.

5	900-00101-00033	A/C	M	UL1015 18AWG PVC 105℃ 600V WHITE OD2.8			
4	900-00101-00087	A/C	M	UL1015 18AWG PVC 105℃ 600V RED OD2.8			
3	900-00101-00032	A/C	M	UL1015 18AWG PVC 105℃ 600V BLACK OD2.8			
2	504-00049-00	A/C	M	ADHESIVE HEAT SHRINK TUBE OD3.2			
1	22003635-01	1	PC	STANDARD SERIES 3PIN PANEL MOUNT WITH FEMALE PIN(4 LOCKS -501)			
ITEM	PART NO	QTY	UNIT	DESCRIPTION			
MATERIAL OF BILL							
PART No.: 11C03622051309		DRAWN BY:		XU	TECHNICS:		
MATERIAL:		PROOFREADED BY:			QUALITY:		
MOLD No.:		CHECKED BY:			APPROVED BY:		
		STANDARDISATION:					

UNIT: mm

DESCRIPTION: STANDARD SERIES 3PIN PANEL MOUNT WITH FEMALE PIN(4 LOCKS -501) L=500MM

SCALE: 1:1 SHEET: 1 OF 1

REV.: C1 SIZE: A4 ASME Y14.5-2009

GB/T 1804-M

CHOGORI®

深圳乔合里科技股份有限公司

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN CHOGORI PERSONNEL WITHOUT AUTHORIZATION FROM CHOGORI CORP.