

1		2		3		4		5		6		7		8	
CUSTOMER No. :		REV .		CATEGORY		IN IINE WITH THE TYPE		PAGE	REV .	ECN&ECR No.	DESCRIPTION		DSN	DATE	
						YES NO			C1	NA	Initial Drawing		XU	2022.05.23	
				NEW ENERGY VEHICLE PRODUCTS		√									
				INDUSTRIAL PRODUCTS		√		1	C2	NA	Change The Length To 1000mm		XU	2022.06.24	
				RoHS		√									
				REACH											
				Halogen-Free		√									
				CALIFORNIA 65		√									
BLACK 1 RED 2 VIEW A P1 19REF 59REF CHOGORI CHOGORI ① ② C2*1000±30 P/N: 22002133-01-001															
SPECIFICATIONS: 1.INSULATION RESISTANCE: 10MΩ@500VDC/0.01S. 2.VOLTAGE RATING: 300V. 3.CURRENT RATING: 10A. 4.OPERATION TEMPERATURE: -40℃~+80℃. 5.WATERPROOF IPX7(MATED). 6.RoHS COMPLIANT. UNIT: mm DESCRIPTION: STANDARD SERIES 2PIN MALE CONNECTOR WITH MALE PIN(4 LOCKS,MOLDING,-501) L= 1000MM SCALE: 1:1 SHEET: 1 OF 1 REV.: C2 SIZE: A4 ASME Y14.5-2009 CHOGORI® 深圳乔合里科技股份有限公司															
<div><div><div>C2</div><div>2</div><div>900-00201-00049</div><div>1.06</div><div>M</div><div>UL2464 2*18AWG VW-1 PVC -40~80℃ 300V BLACK OD5.5</div></div><div><div>1</div><div>22002133-01-001</div><div>1</div><div>PC</div><div>STANDARD SERIES 2PIN MALE CONNECTOR WITH MALE PIN(4 LOCKS,MOLDING,-501)</div></div><div><div>ITEM</div><div>PART NO</div><div>QTY</div><div>UNIT</div><div>DESCRIPTION</div></div><div><div colspan="6">MATERIAL OF BILL</div><div><div>PART No.:</div><div>11C03622051301</div><div>MATERIAL:</div><div>MOLD No.:</div></div><div><div>DRAWN BY:</div><div>XU</div><div>TECHNICS:</div><div></div></div><div><div>PROOFREADED BY:</div><div></div><div>QUALITY:</div><div></div></div><div><div>CHECKED BY:</div><div></div><div>APPROVED BY:</div><div></div></div><div><div>STANDARDISATION:</div><div></div><div></div><div></div></div></div></div>															
1		2		3		4		5		6		7		8	

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN CHOGORI PERSONNEL WITHOUT AUTHORIZATION FROM CHOGORI CORP.