

8

7

6

5

4

3

2

1

Part Number	Length (Meters)
CA0911A800801012	1 (3.28 FEET)
CA0911A800802012	2 (6.56 FEET)
CA0911A800803012	3 (9.84 FEET)
CA0911A800805012	5 (16.40 FEET)
CA0911A800807012	7 (22.96 FEET)
CA0911A800810012	10 (32.80 FEET)
CA0911A800813012	13 (42.65 FEET)
CA0911A800815012	15 (49.21 FEET)

LENGTH (Mxx)

69.5 (2.73 in)

M 16 x0.75

25MM SCREEN

76.2MM (3")

CA0911B8008XX012

() METERS

WWW.AMPHENOL-SINE.COM

AMPHENOL

MALE CONNECTOR PLUG

WIRING DIAGRAM

BLACK (22 AWG)

RED (22 AWG)

WHITE (22 AWG)

GREEN (22 AWG)

BROWN(22 AWG)

BLUE (22 AWG)

ORANGE(22 AWG)

YELLOW(22 AWG)

1

2

3

4

5

6

7

8

FACE VIEW

CAN BE USED WITH MATING FEMALE RECEPTACLE # CA0911F118005

CONTACT YOUR DISTRIBUTOR FOR OTHER MATING OPTIONS

TECHNICAL DATA:

1) MATERIALS:

COUPLING NUT: ZINC DIE CAST

INSULATION INSERT: THERMOPLASTIC

CONTACT: SILVER PLATED

OVERMOLD MATERIAL: THERMOPLASTIC COLOR: BLACK

CABLE RATING: UL LISTED, UL RECOGNIZED AWM STYLE AND CSA CERTIFIED, AWM 2517 105°C 300V

CABLE JACKET MATERIAL: PVC COLOR: BLACK

BENDING RADIUS: 0.260"

CONDUCTOR INSULATION: SR-PVC

NUMBER OF CONDUCTORS: (8) 22AWG

2) CONNECTOR ELECTRICAL DATA:

CURRENT (MAX): 7A AT 40°C

VOLTAGE (MAX): 250V AC/DC PER UL 1977

INSULATION RESISTANCE: 100M OHMS PER IEC 60512-3-1

RATED IMPULSE WITHSTAND VOLTAGE: 1200V PER IEC 60664-1

3) CONNECTOR MECHANICAL DATA:

TEMPERATURE RANGE: -25°C TO +100°C

PROTECTION: IP67/IP68 (PER MATED CONDITION)

MATING CYCLES: >500

4) RoHS COMPLIANT

TOLERANCE

0-2.99 M = +100.0/-25.0mm	0-9.99 FT = +4" / -1"
3-8.99 M = +150.0/-25.0mm	10.00-29.99 FT = +6" / -1"
9-14.99 M = +300.0/-25.0mm	30.00-49.99 FT = +12" / -1"
15-OVER M = +450.0/-25.0mm	50 FT-OVER = +18" / -1"

INDUSTRIAL@AMPHENOL

TRUSTED GLOBALLY

QUANTITY

PART NUMBER

DESCRIPTION

ITEM

UNLESS OTHERWISE SPECIFIED

1) All dimensions are in metric(mm).

2) Tolerances are as follows:

1 PL DEC ±0.30

2 PL DEC ±0.15

3 PL DEC ±0.08

3) Note reference =

SIGNATURES

DRAWN

CHECKED

ENGINEER

APPROVAL

DATE

6-JUNE-17

8-JUNE-17

13-JUNE-17

MATERIAL SPECIFICATIONS:

PROCESS SPECIFICATIONS:

IPC-WHMA-A-620

NEXT ASSY:

MATERIALS LIST

Amphenol

Sine Systems - www.amphenol-sine.com

44724 Morley Drive

Clinton Township, MI 48036

C091 (M16) 8 POS CIRCULAR MOLDED, STD.

STRAIN RELIEF, MALE TO LEADS, 22AWG, 4 PAIR, FOIL SHIELD

THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.

SIZE

TYPE

DRWG NO.

REVISION

C-

CA9811A8008XX012

A1

SCALE

HALF

CA9811A8008XX012

SHEET

1

OF

1