

1		2		3		4		5		6		7		8	
CUSTOMER No. :		REV. :		CATEGORY		IN LINE WITH THE TYPE		PAGE	REV. :	ECN&ECR No.	DESCRIPTION		DSN	DATE	
						YESNO			C1	NA	Initial Drawing		XU	2022.07.18	
				NEW ENERGY VEHICLE PRODUCTS		√									
				INDUSTRIAL PRODUCTS		√									
				RoHS		√									
				REACH											
				Halogen-Free											
				CALIFORNIA 65		√									

15±0.1

Ø16.0±0.1

Panel Cut-Out

RED 2

BLACK 1

VIEW A

19REF

Panel T=2.5Max

10REF

P1

*500±30

①

②

③④

P/N: 22002635-01

SPECIFICATIONS:

1.INSULATION RESISTANCE : 10MΩ@500VDC/0.01S.

2.VOLTAGE RATING : 600V.

3.CURRENT RATING : 10A.

4.OPERATION TEMPERATURE : -10℃~+105℃.

5.WATERPROOF IPX7(MATED).

6.RoHS COMPLIANT.

UNIT: mm

DESCRIPTION:
STANDARD SERIES 2PIN PANEL MOUNT
WITH FEMALE PIN(4 LOCKS -501) L=500MM

SCALE: 1:1

SHEET: 1 OF 1

GB/T 1804-M

REV.: C1

SIZE: A4

ASME Y14.5-2009

CHOGORI®

深圳乔合里科技股份有限公司

4	900-00101-00087	A/C	M	UL1015 18AWG PVC 105℃ 600V RED OD2.8
3	900-00101-00032	A/C	M	UL1015 18AWG PVC 105℃ 600V BLACK OD2.8
2	504-00049-00	A/C	M	ADHESIVE HEAT SHRINK TUBE OD3.2
1	22002635-01	1	PC	STANDARD SERIES 2PIN PANEL MOUNT WITH FEMALE PIN(4 LOCKS -501)
ITEM	PART NO	QTY	UNIT	DESCRIPTION
MATERIAL OF BILL				
PART No.: 11C03622051306		DRAWN BY:		XU
MATERIAL:		PROOFREADED BY:		QUALITY:
MOLD No.:		CHECKED BY:		APPROVED BY:
		STANDARDISATION:		

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN CHOGORI PERSONNEL WITHOUT AUTHORIZATION FROM CHOGORI CORP.