

1		2		3		4		5		6		7		8	
CUSTOMER No. :		REV .		CATEGORY		IN IINE WITH THE TYPE		PAGE	REV .	ECN&ECR No.	DESCRIPTION		DSN	DATE	
						YES NO			C1	NA	Initial Drawing		XU	2022.05.24	
				NEW ENERGY VEHICLE PRODUCTS											
				INDUSTRIAL PRODUCTS		√									
				RoHS		√									
				REACH											
				Halogen-Free		√									
				CALIFORNIA 65		√									

Panel Cut-Out

15±0.1

Ø16.0±0.1

VIEW A

BLACK 1

RED 2

29.5REF

Panel T=2.5Max

17REF

P1

CHOGORI

①

*500±30

②③

P/N: 22002535-01-001

SPECIFICATIONS:

1.INSULATION RESISTANCE: 10MΩ@500VDC/0.01S.

2.VOLTAGE RATING: 600V.

3.CURRENT RATING: 10A.

4.OPERATION TEMPERATURE: -10℃~+105℃.

5.WATERPROOF IPX7(MATED).

6.RoHS COMPLIANT.

3	900-00101-00087	A/C	M	UL1015 18AWG PVC 105℃ 600V RED OD2.8
2	900-00101-00032	A/C	M	UL1015 18AWG PVC 105℃ 600V BLACK OD2.8
1	22002535-01-001	1	PC	STANDARD SERIES 2PIN PANEL MOUNT WITH MALE PIN(4 LOCKS,MOLDING,-501)

ITEM	PART NO	QTY	UNIT	DESCRIPTION
MATERIAL OF BILL				
PART No.: 1IC03622051303		DRAWN BY:	XU	TECHNICS:
MATERIAL:		PROOFREADED BY:		QUALITY:
MOLD No.:		CHECKED BY:		APPROVED BY:
		STANDARDISATION:		

UNIT: mm

⊕

⌵

未注线性和角度尺寸公差
UNSPECIFIED TOLERANCE

GB/T 1804-M

DESCRIPTION:
STANDARD SERIES 2PIN PANEL MOUNT WITH
MALE PIN(4 LOCKS,MOLDING,-501) L=500MM

SCALE: 1:1

SHEET: 1 OF 1

REV.: C1

SIZE: A4

ASME Y14.5-2009

CHOGORI®

深圳乔合里科技股份有限公司

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TU YOU ON CONDITION THAT NO FURTHER DICLOSURE IS MADE BY YOU TO OTHER THAN CHOGORI PERSONNEL WITHOUT AUTHORIZATION FROM CHOGORI CORP.