





LOC	DIST	REVISIONS					
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			A	RELEASED PER ECO-10-012478	24JUNE2010	DH	DY
			B1	REV PER ECO-20-004668	21APR2020	ML	SZ

- 1 MATERIAL
HOUSING: POLYESTER, COLOR, GRAY, UL 94V-0.
CONTACT: PHOSPHOR BRONZE, HIGH CURRENT COPPER ALLOY.
- 2 FINISH
IN ACCORDANCE WITH PRODUCT SPECIFICATION 108-1651,
GOLD PLATING OR EQUIVALENT PLATING ON PRODUCT CONTACT MATING AREA,
AND MATTE TIN PLATING ON COMPLIANT PIN AREA, ALL OVER MATTE NICKEL
UNDERPLATED. DETAIL PLEASE REFER TO PRODUCT SPECIFICATION 108-1651.
- 3 TOLERANCE TO BE ± 0.25 BEFORE CONNECTOR IS APPLIED TO PC BOARD.
- 4 REFERENCE APPLICATION SPEC 114-1103 FOR
RECOMENDED PLATED THRU HOLE DIAMETER AND
PLATING THICKNESS.
5. CURRENT RATING 16A/CONTACT PER PRODUCT SPEC 108-1651.



9	29.95	8	1645498-7
8	26.95	7	1645498-6
7	23.95	6	1645498-5
6	20.95	5	1645498-4
5	17.95	4	1645498-3
4	14.95	3	1645498-2
3	11.95	2	1645498-1
POSITION B REF		A	PART NUMBER

THIS DRAWING IS UNPUBLISHED. IT IS SUBJECT TO CHANGE WITHOUT NOTICE. ANY CHANGES TO THIS DRAWING SHOULD BE CONTACTED FOR THE LATEST REVISION.				DWN	B. CARBO	18NOV2008	Tyco Electronics Harrisburg, PA 17105-3608				
TOLERANCES UNLESS OTHERWISE SPECIFIED:				CHK	G. GRIFFITH	18NOV2008	NAME				
DIMENSIONS:				APVD	G. GRIFFITH	18NOV2008	PRODUCT SPEC 108-1651 APPLICATION SPEC 114-1103 WEIGHT - RESTRICTED CUSTOMER				
mm				108-1651		APPLICATION SPEC					
0 PLC ± .01				114-1103		WEIGHT					
1 PLC ± .01				-		RESTRICTED CUSTOMER					
2 PLC ± .01				-		SCALE					
3 PLC ± .01				-		SHEET					
4 PLC ± .01				-		OF					
ANGLES				-		REV					
FINISH				-		B1					