








D



C

B



D

C

B

A

PRODUCT HAS NOT COMPLETED
QUALIFICATION TESTING

NOTES:

- 1 PLATING: 0,5µm MIN. TIN OVER NICKEL.
- 2 PLATING:

PARTNUMBER	PERFORMANCE LEVEL
1551012-1	PERFORMANCE LEVEL 1: CONNECTOR TESTED AND QUALIFIED AGAINST TELCORDIA GR-1217-CORE QUALITY LEVEL III: UNCONTROLLED ENVIRONMENT APPLICATIONS. SEE PRODUCT SPEC 108-19353
1551012-2	PERFORMANCE LEVEL 2: CONFORMS TO ALL TESTING ACCORDING PRODUCT SPEC 108-19320, -250 MATING CYCLES, 4 DAYS MIXED GAS TEST PER IEC 60068-2-60 METHOD I

- 3 CONSULT APPLICATION SPEC OR CONTACT TE CONNECTIVITY FOR PERMISSIBLE CONTACT ASSIGNMENTS.
- 4 CONNECTOR MARKED WITH PARTNUMBER AND DATE CODE.
- 5 FOR PC-BOARD ROUTING RECOMMENDATIONS SEE SPEC 114-19140

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	Vathsa	01 Dec 08
DIMENSIONS:		CHK	RA	01 Dec 08
mm		APVD	MW	01 Dec 08
		PRODUCT SPEC		
		SEE NOTE 2		
		APPLICATION SPEC		
MATERIAL		114-19106		
		WEIGHT		
		-		
		CUSTOMER DRAWING		
		SCALE		
		5:1		
		SHEET		
		1 OF 1		
		REV		
		A		

3	OVERMOLD	LCP 30% GF NATURAL
2	HOUSING	LCP 30% GF NATURAL
1	CONTACT	COPPER ALLOY
ITEM NO.	DESCRIPTION	MATERIAL

NAME				MALE CONNECTOR	
				Z-PACK Slim UHD	
				-	
SIZE	CAGE CODE	DRAWING NO		RESTRICTED TO	
A2	00779	C-1551012		-	

A