

4

3

2

1

THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION
© COPYRIGHT - TE Connectivity Ltd.	ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
G		REVISED PER ECO-18-007010	23MAY18	KH	MZ

RAISED INDICATOR
ARROW

THREAD START
12° OFF CTR

16.13
[.635]

9.14 MAX
[.360]

SEALING GASKET
ELASTOMER, BLACK
1.57[.062] THK

DRIVE STUD
CARBON STEEL
NICKEL PER
QQ-N-290

DUST CAP
ZINC PER QQ-Z-363 DIE CAST
NICKEL PER QQ-N-290 OVER
COPPER PER MIL-C-14550

DETENT
THERMOPLASTIC
BLACK

PART NUMBER AND
DATE CODE MARKED
ON ANY OF THESE
SURFACE

BEAD CHAIN
STEEL
NICKEL PER
QQ-N-290


COUPLING BOTH ENDS
BRASS
NICKEL PER QQ-N-290

55.12
[2.170]
DIA

76.20 ± .188
[3.000 ± .188]

1 BEADED PORTION OF CHAIN MUST ROTATE FREELY. THE EYELET OF THE CHAIN IS NOT REQUIRED TO SPIN FREELY AROUND THE STUD.

211904-1
PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R.SHIREY	08/13/91	 TE Connectivity Ltd.	
DIMENSIONS: mm [INCHES]		CHK —	—		
	TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD —	NAME PROTECTIVE CAP ASSEMBLY, SIZE 28, CMC	
	0 PLC ± —		PRODUCT SPEC —		
	1 PLC ± —		APPLICATION SPEC —		
	2 PLC ± 0.25[.010]		—		
MATERIAL SEE CALLOUTS		FINISH SEE CALLOUTS	WEIGHT 0	SIZE A2	CAGE CODE 00779
			CUSTOMER DRAWING	DRAWING NO C-211904	RESTRICTED TO —
			SCALE 2:1	SHEET 1 of 1	REV G